



AL WATANIA GYPSUM SOLUTIONS

Watani UniRock

All purpose joint compound



✓ DESCRIPTION

WATANI All-Purpose Joint Compound is a pre-mixed compound that air-dries and is specifically formulated to fill drywall, repair cracks, conceal screws, and skim-coating interior gypsum board systems.

✓ STANDARD REFERENCE

ASTM C475, ASTM C840

✓ Protective Measures



Does not pose fire hazard



Consistent high-quality



Not classified as hazard transportation



Stable Non-reactive with surrounding material



Non-Hazardous



Certified



First Air Measure

✓ STORAGE AND HANDLING

- > Store at 13-35°C (55-95°F) in a dry environment.
- > Protect from extreme cold and heat as well as exposure to direct sunlight.
- > Keep the container tightly sealed.
- > Stored under proper conditions for one-year maximum, starting from the manufacturing date.

✓ APPLICATIONS

Start by applying the initial layer of WATANI to the joints, ensuring complete coverage of the joint tape. Allow 2 hours for drying, then apply a second layer with a width of 20 cm. After the second layer has dried, proceed to apply the third and final layer, making sure it has a width of 30 cm. Always adhere to the maximum jointing thickness of 2 mm and verify that the product is properly applied before moving to skimming.

✓ STANDARD REFERENCE

Manufactured according to ASTM & EN standard

✓ DATA SHEET

PROPERTY	UNIT	VALUE
No Cracks 50mm zone	-	No cracks
Drying Time	Hours	24
pH	-	8.5:10
Practical Size Distribution	200µm sieve	≤1%
Adhesive strength	N/mm ²	≥0.25
Low VOC content	g/L	3
Standard	-	EN 13963
Coverage per 28 kg bucket	m ²	46-56



MANUFACTURER INFORMATION
AL WATANIA GYPSUM CO
Yanbu, Western Saudi Arabia
www.w-gypsum.com

2025 TDS/ JC
www.w-gypsum.net